



**BUREAU  
VERITAS**

**Bureau Veritas  
Consumer Products Services  
Germany GmbH**

Businesspark A96  
86842 Türkheim  
Germany  
+ 49 (0) 40 740 41 - 0  
cps-tuerkheim@de.bureauveritas.com

Certification body of BV CPS GmbH  
Accredited according to EN 45011 -  
ISO / IEC Guide 65

# Certificate

**Manufacturer / applicant:** SolarEdge Technologies Ltd.  
6 HeHarash St.  
Hod Hasharon 45240  
Israel

**Product type:** DC-DC converter for mounting on photovoltaic panels

**Modell:** OPxxx-LV  
OPxxx-MV  
OPxxx-96V  
Pxxx  
PxxxI

**Remark:** xxx can be any number from 0 – 9 up to the max. input power.  
For more details see annex of this certificate.  
The Power Optimizer Pxxx with IP 65 Enclosure can also have  
an “I” as a suffix showing the independent function without  
SolarEdge inverters

A representative test sample of the aforementioned product was tested according to

**Applicable standards:** IEC 62109-1:2010, EN 62109-1:2010, DIN EN 62109-1:2011

**BV project number:** 12TH0377

**Certificate number:** 13-156

**Date of issue:** 2013-11-20

**Certification body**

Dieter Zitzmann

(A partial representation of the certificate requires  
the written permission of BV CPS GmbH)



Deutsche  
Akkreditierungsstelle  
D-ZE-12024-01-01



QUALITY



HEALTH



SAFETY



ENVIRONMENT



SOCIAL  
ACCOUNTABILITY



**BUREAU  
VERITAS**

**Bureau Veritas  
Consumer Products Services  
Germany GmbH**

Businesspark A96  
86842 Türkheim  
Germany  
+ 49 (0) 40 740 41 - 0  
cps-tuerkheim@de.bureauveritas.com

Certification body of BV CPS GmbH  
Accredited according to EN 45011 -  
ISO / IEC Guide 65

## Annex to Certificate 13-156

Ratings:	OPxxx-LV OPIxxx-LV	OPxxx-MV	OPxxx-96V OPIxxx-96V
Max. input power [W]:	250 - 300	400	600
Input DC voltage range [V]:	0 – 55	0 – 75	0 – 96
Input DC current [A]:	10		
Output DC voltage [V]:	0 - 60		0 – 85
Max. output DC current [A]:	15		
Enclosure type:	SAOB IP65		

Ratings:	Pxxx				
Max. input power [W]:	300	350	500	600	700
Input DC voltage range [V]:	8 – 48	8 – 60	8 – 80	12,5 – 96	12,5 – 125
Input DC current [A]:	10				
Output DC voltage [V]:	0 – 60	0 – 70	0 – 85		
Max. output DC current [A]:	15				
Enclosure type:	SAOB IP65 / NAOB IP67			SAOB IP65	

Remark:	xxx can be any number from 0 – 9 up to the max. input power The Power Optimizer Pxxx with IP 65 Enclosure can also have an “1” as a suffix showing the independent function without SolarEdge inverters
---------	--

